

PFFY-P-VLRM-E

Floor Standing Concealed Indoor Unit

A compact concealed unit providing simple, effective air conditioning in perimeter zones. The unit is easy to install and at only 220mm deep offers an unobtrusive method of delivering highly efficient air-conditioning performance.

- Concealed unit for hidden installation
- Ideal for perimeter refurbishments
- Cooling operation set temperature can be set down to 14°C db



Technical Information

PFFY-P-VLRM-E - INDOOR UNITS

MODEL REFERENCE		PFFY-P20VLRM-E	PFFY-P25VLRM-E	PFFY-P32VLRM-E	PFFY-P40VLRM-E	PFFY-P50VLRM-E	PFFY-P63VLRM-E
CAPACITY (kW)	Heating (nominal)	2.5	3.2	4.0	5.0	6.3	8.0
	Cooling (nominal)	2.2	2.8	3.6	4.5	5.6	7.1
	HP Heating (UK)	2.5	3.2	4.0	5.0	6.3	8.0
	COP P Heating (UK)	2.3	3.0	3.7	4.7	5.9	7.5
	Cooling (UK)	2.1	2.7	3.4	4.3	5.3	6.7
	High Sensible	Cooling (UK)	1.6	2.0	2.6	3.3	4.1
SHF	(UK)	0.81	0.70	0.74	0.72	0.74	0.73
High Sensible	(UK)	0.88	0.80	0.81	0.79	0.80	0.79
POWER INPUT (kW)	Heating (nominal)	0.04	0.04	0.06	0.065	0.085	0.10
	Cooling (nominal)	0.04	0.04	0.06	0.065	0.085	0.10
AIRFLOW (m3/min)	Lo-Hi	5.5-6.5	5.5-6.5	7-9	9-11	12-14	12-15.5
NOISE (dBA)	Lo-Hi	34-40	34-40	35-40	38-43	38-43	40-46
WEIGHT (kg)		18.5	18.5	20	21	25	27
DIMENSIONS (mm)	Width	886	886	1006	1006	1246	1246
	Depth	220	220	220	220	220	220
	Height	639	639	639	639	639	639
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz	220-240v, 50Hz
PHASE		Single	Single	Single	Single	Single	Single
RUNNING CURRENT (A)	Heating	0.19	0.19	0.29	0.32	0.40	0.46
	Cooling	0.19	0.19	0.29	0.32	0.40	0.46
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6
MAINS CABLE No. Cores		3	3	3	3	3	3